

ALUMAX DRILL

Jobber length

Ø	Overall Length	Flute Length	Pack QTY	Price £ each	Ø	Overall Length	Flute Length	Pack QTY	Price £ each	Ø	Overall Length	Flute Length	Pack QTY	Price £ each
*0,8	30	10	10	2.45	4,3	80	47	10	2.59	9,5	125	81	5	7.64
*0,85	30	10	10	3.06	4,4	80	47	10	2.59	9,6	133	87	5	13.58
*0,9	32	11	10	2.42	4,5	80	47	10	2.75	9,7	133	87	5	13.75
*0,95	32	11	10	2.90	4,6	80	47	10	2.59	9,8	133	87	5	13.75
*1,0	34	12	10	2.22	4,7	80	47	10	2.59	9,9	133	87	5	14.09
*1,05	34	12	10	3.11	4,8	86	52	10	2.59	10,0	133	87	5	8.26
*1,1	36	14	10	2.24	4,9	86	52	10	2.59	10,2	133	87	5	14.59
*1,15	36	14	10	2.94	5,0	86	52	10	2.88	10,5	133	87	5	9.87
*1,2	38	16	10	2.46	5,1	86	52	10	2.84	11,0	142	94	5	11.91
*1,25	38	16	10	2.90	5,2	86	52	10	2.84	11,2	142	94	5	23.12
*1,3	38	16	10	2.36	5,3	86	52	10	2.84	11,5	142	94	5	13.59
*1,35	40	18	10	2.77	5,4	93	57	10	3.61	12,0	151	101	5	15.07
*1,4	40	18	10	2.20	5,5	93	57	10	3.33	12,5	151	101	5	16.56
*1,45	40	18	10	2.59	5,6	93	57	10	3.69	13,0	151	101	5	17.01
*1,5	40	18	10	2.05	5,7	93	57	10	3.69					
*1,55	43	20	10	2.42	5,8	93	57	10	3.63					
*1,6	43	20	10	2.42	5,9	93	57	10	3.69					
*1,65	43	20	10	2.86	6,0	93	57	10	3.63					
*1,7	43	20	10	2.28	6,1	101	63	10	3.93					
*1,75	46	22	10	3.29	6,2	101	63	10	3.93					
*1,8	46	22	10	2.28	6,3	101	63	10	4.23					
*1,85	46	22	10	2.69	6,4	101	63	10	4.25					
*1,9	46	22	10	2.31	6,5	101	63	10	4.05					
*1,95	49	24	10	2.72	6,6	101	63	10	4.81					
*2,0	49	24	10	1.89	6,7	101	63	10	4.85					
*2,05	49	24	10	2.37	6,8	109	69	10	4.93					
*2,1	49	24	10	2.36	6,9	109	69	10	4.93					
*2,15	53	27	10	2.78	7,0	109	69	10	4.39					
*2,2	53	27	10	2.36	7,1	109	69	10	6.93					
*2,25	53	27	10	3.42	7,2	109	69	10	6.93					
*2,3	53	27	10	2.36	7,3	109	69	10	6.93					
*2,35	53	27	10	2.78	7,4	109	69	10	6.93					
*2,4	57	30	10	2.39	7,5	109	69	10	5.33					
*2,45	57	30	10	2.81	7,6	117	75	10	7.45					
2,5	57	30	10	1.64	7,7	117	75	10	7.45					
2,6	57	30	10	1.97	7,8	117	75	10	7.45					
2,7	61	33	10	2.03	7,9	117	75	10	8.42					
2,8	61	33	10	2.03	8,0	117	75	10	5.63					
2,9	61	33	10	2.03	8,1	117	75	5	8.77					
3,0	61	33	10	1.81	8,2	117	75	5	9.11					
3,1	65	36	10	1.89	8,3	117	75	5	9.11					
3,2	65	36	10	1.87	8,4	117	75	5	9.28					
3,3	65	36	10	1.87	8,5	117	75	5	6.05					
3,4	70	39	10	1.99	8,6	125	81	5	9.63					
3,5	70	39	10	2.10	8,7	125	81	5	10.65					
3,6	70	39	10	1.99	8,8	125	81	5	10.65					
3,7	70	39	10	1.99	8,9	125	81	5	10.83					
3,8	75	43	10	2.13	9,0	125	81	5	6.88					
3,9	75	43	10	2.13	9,1	125	81	5	12.03					
4,0	75	43	10	2.16	9,2	125	81	5	12.03					
4,1	75	43	10	2.13	9,3	125	81	5	12.03					
4,2	75	43	10	2.11	9,4	125	81	5	12.03					

*Sizes are 814 3 9 9 1



**EXTENDED
SIZE RANGE**

HSS

DIN 338

Geometry optimised for high penetration rates in light alloys.

Also available in:

Long Series
Type 814 O 3 8 1

Taper Shank
Type 814 1 O 2 1

	Unalloyed Steel 200-400 N/mm ²	Short Chipping Non-ferrous Alloys	Long Chipping Non-ferrous Alloys
Cutting speed	26 M/min	30 M/min	60 M/min
Feed rate mm/rev	Ø2	0.04	0.03
	Ø4	0.08	0.06
	Ø6	0.13	0.09
	Ø8	0.17	0.12
	Ø10	0.21	0.15
Ø12	0.25	0.18	