



UNF
Product no. 805 215 1

SPIRAL FLUTE TAP - 2B

HSS-E		DIN 371					
Ø	P	Drill Ø	Overall Length	Thread Length	Shank Ø	Square ■	Price £ each
N°4	48	2,4	56	11	3,5	2,7	19.09
N°5	44	2,7	56	11	3,5	2,7	19.09
N°6	40	3	56	11	4	3	19.47
N°8	36	3,5	63	12	4,5	3,4	19.47
N°10	32	4,1	70	14	6	4,9	19.47
N°12	28	4,6	80	14	6	4,9	19.09
1/4	28	5,5	80	16	7	5,5	14.77
5/16	24	6,9	90	18	8	6,2	17.01
3/8	24	8,5	90	18	9	7	19.59

General purpose cobalt tap, suitable for blind holes in a wide range of materials.

Various coatings available.

Price and delivery on request.



UNF
Product no. 805 219 1

SPIRAL FLUTE TAP - 2B

HSS-E		DIN 374					
Ø	P	Drill Ø	Overall Length	Thread Length	Shank Ø	Square ■	Price £ each
7/16	20	9,9	100	22	8	6,2	25.11
1/2	20	11,5	110	25	9	7	26.72
9/16	18	12,9	110	25	11	9	33.09
5/8	18	14,5	110	25	12	9	36.75
3/4	16	17,5	125	32	14	11	47.27
7/8	14	20,5	125	32	18	14,5	72.31
1	12	23,3	140	32	20	16	88.99

General purpose cobalt tap, suitable for blind holes in a wide range of materials.

Various coatings available.

Price and delivery on request.



UNF
Product no. 22169

SPIRAL FLUTE TAP - 6H Steam Oxide Coated

HSSE-V3		DIN 371					
Ø	P	Drill Ø	Overall Length	Thread Length	Shank Ø	Square ■	Price £ each
N°4	48	2,4	56	5	3,5	2,7	14.76
N°5	44	2,7	56	5	3,5	2,7	14.59
N°6	40	3	56	6	4	3	13.89
N°8	36	3,5	63	8	4,5	3,4	14.16
N°10	32	4,1	70	8	6	4,9	15.11
N°12	28	4,6	80	9	6	4,9	17.32
1/4	28	5,5	80	10	7	5,5	15.63
5/16	24	6,9	90	12	8	6,2	17.55

Special design for blind holes in stainless steels and other 'sticky' materials. Chamfered relief and surface treatment reduces chipping.



UNF
Product no. 32169

SPIRAL FLUTE TAP - 6H Steam Oxide Coated

HSSE-V3		DIN 374					
Ø	P	Drill Ø	Overall Length	Thread Length	Shank Ø	Square ■	Price £ each
3/8	24	8,5	90	12	7	5,5	19.03
7/16	20	9,9	100	14	8	6,2	25.56
1/2	20	11,5	100	16	9	7	26.70
9/16	18	12,9	100	20	11	9	36.49
5/8	18	14,5	100	20	12	9	34.83
3/4	16	17,5	110	25	14	11	44.91
7/8	14	20,4	125	25	18	14,5	53.96
1	12	23,3	140	28	18	14,5	73.74

Special design for blind holes in stainless steels and other 'sticky' materials. Chamfered relief and surface treatment reduces chipping.

